Aqua DT Matt

WATER-DILUTABLE, DIRECT-ADHESION TOPCOAT ENAMEL FOR INTERIOR AND EXTERIOR USE

- → Direct-adhesion
- → Spreads very well
- → Excellent coverage and adhesion



IMPA CONTEMPORARY IDEAS

INNOVATING SURFACES FOR ***BUILDING***

Aqua DT Matt 0654

90006111-10/26

WATER-DILUTABLE, DIRECT-ADHESION TOPCOAT ENAMEL FOR INTERIOR AND EXTERIOR USE



Water-based enamel featuring direct-adhesion technology; it offers rapid drying, ease of application, excellent flow, and high hiding power. The dried film is resistant to atmospheric agents and possesses good elasticity.

It can be applied both indoors and outdoors to various types of substrates, including iron, alloys, galvanized sheet metal, wood, and PVC. It is also suitable for application on glass, but only for interior systems.

Tools

Brush, Short-napped or microfiber roller, Spray

Technical features

Appearance	matt 10-15 gloss (Gardner 60°)
Recommended thicknesses	60 µm dey film
Air drying	20 min, dust free 8 h, touch dry 24-36 h, through drying
Recoating	4-5 h
→ Dilution	brush/roller: 5-10% with water by weight/volume spray: 10-15% with water by weight/volume
→ Cover rate	4 m²/l with a dry film thickness of 60 µm

Application

INTERIOR CYCLES

Direct-adhesion to ferrous substrates, alloys and galvanized sheet metal, wood, PVC, glass or old, well-adhered paints.
Apply 2 or 3 coats of AQUA DT MATT

EXTERIOR CYCLES

IRON AND WOODEN SURFACES:
Refer to the section on substrate preparation in the Technical Data Sheet.

GALVANIZED SURFACES, ALUMINUM, ALLOYS AND PVC:
Direct-adhesion to galvanized surfaces, Aluminium, Alloys and PVC.
Apply 2 coats of AQUA DT MATT.

Thorough cleaning of the substrate is a precondition for the positive outcome of the painting

AUTHORIZED DEALER

IMPA S.p.A. Unipersonale – Via Crevada, 9/E
31020 San Pietro di Feletto TV – ITALY
T +39 0438 4548
info@impa.it – www.impa.it

Company under the management
and coordination of Fassa S.r.l.