



0319 CLASS PLUS

NON-DRIP WASHABLE WALL PAINT, FOR APPLICATION EVEN ON PLASTERBOARD



Advantages

- Non-drip
- Very matt appearance
- The product complies with CAM 2025 requirements for indoor use

Description and Use

CLASS PLUS is a non-drip washable emulsion paint based on vinyl resins, easy to apply, offering high hiding power and a strong white colour.

It features good abrasion resistance and a velvet matt appearance.

It is recommended for interior masonry surfaces, new or in need of repainting, even with high absorption such as plasterboard; it can also be used in outdoor sheltered applications, and wherever average weather and environmental conditions will allow for it.

The product can be coloured using ADVANCE HT tinting system.

In the black colour the product is part of a paint system in compliance with the fire protection requirements of marine Equipment Directive MED 2014/90/EU including the requirements and testing standards of Regulation (EU) 2024/1975.

The product also complies with the award requirements according to the Ministerial Decree of 24 November 2025 (CAM 2025 Edilizia): low VOC and ISO 14001 certified company.

Substrate preparation

The substrate must be cured, not chalking and clean (without grease, oil or other polluting agents).

For degraded surfaces, remove all traces of old peeling paint and any efflorescence.

In case of mould or algae growth, carry out a treatment with DECISO code 0610.

On plaster, level any unevenness with a suitable levelling compound, and allow the treated areas to rest; fill and rub down holes, cracks and crackles with IMPASTUK UNIVERSAL EXTRA code 0401.

On new, powdery or highly absorbing plaster, on fillings or old flaking paints, apply one layer of masonry fixative to make uniform the substrate absorption. Indoors, use the water-reducible products POLY ACRYL code 0004, or SUPERFIX code 0010 or GREY FIX code 0011, properly reduced. Outdoors, use the solvent-type ready-to-use CLIM-O-PAINT PRO code 1004, or SUPERFIX or GREY FIX.

Once dried, continue applying two coats of CLASS PLUS.

Application

Application method:

- brush
- roller
- spray
- airless

Product preparation:

Mix to achieve even colour and consistency.

Dilution:

by weight: 25-30% water for the first coat, 20-25% for the second one.

by volume: 35-40% for the first coat, 30-35% for the second one.

When using Base ED, dilution should be reduced by 50%.

Recoating:

wait 5-6 hours between the two coats.

Storage life

PROTECT FROM FROST. Store the packaged product at a temperature between +5°C and +35°C.

If stored in a cool, dry place, away from sources of heat and sheltered from sunlight, in its sealed original packaging, the product has a shelf life of 24 months. Check the product's shelf life by referring to the production batch number shown on the packaging. The batch number is made of eight numeric characters in which the first four digits identify the year and month of production. Once the shelf life has expired, it must be disposed of in accordance with current legislation.

Technical features

Colour	white
Appearance of the dry film	very matt (UNI 10795)
Specific weight	1.57 kg/l (± 0.02)
Viscosity	15000-20000 mPa.s Brookfield
Product emissions rating in accordance with French Republic decree of 19 April 2011	Class A+
Resistance to washing	excellent (UNI 10795) >5000 Gardner cycles (UNI 10560)
Practical cover rate *	5-6 m²/l per two coats
EU limit value of VOC content (Directive 2004/42/EC)	Cat. A/a, WB: Max VOC 30 g/l product VOC < 30 g/l
* The yield may vary according to the roughness and absorption of the substrate and in relation to the application system used.	
The data are measured at a temperature of 20°C.	
Classification EN 13300	
Wet-scrub resistance	Class 2 (ISO 11998)
Hiding power	Class 1 at a spreading rate of 6 m²/l (EN ISO 6504-3)
Specular gloss	85°, very matt <5 (ISO 2813)

Warnings

- Product recommended for expert users.
- Always read the safety data sheet before use.
- Solvents or thinners used for cleaning tools, as well as any product residues, must not be released into the environment or poured down domestic drains. The recipient/product/thinner or cleaning solvent must be disposed of in accordance with national regulations.
- Surface and ambient temperature must be above + 5 (41°F) and below 35°C (95°F).
- Acquire all the material required to finish the work of the same batch.
- During use, ventilate the room well and use water to clean tools.
- The information provided on this technical datasheet is based on our technical and practical knowledge and experience. The technical data refer to the average characteristics of the basic product and are determined under controlled laboratory conditions. The variability of the natural raw materials available on the market and the tinting of the product can lead to slight deviations in the declared values, in the colour and in the aesthetic effects obtained. It is therefore necessary for the purchaser/user to personally verify, before application, the suitability of the product for the intended use, in particular when different lots of the same material are used in the same job/site.

Do not apply in foggy or rainy weather, or with a RH greater than 75%.

The above mentioned data are meant to facilitate our customers in the use of our products. IMPA is not responsible for applications of products carried out beyond its direct control. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE at assistenza.technica@impa.it.